

## Datasheet | BTG T Thermal

### Product Description

Technogel® represents a dimensionally stable polyurethane gel which, due to its chemical structure, is characterized particularly by the following material property profile.

### Product Properties

- dimensionally stable
- good absorption of shear forces
- very good buffering capacity
- good pressure distribution
- non-irritating to the skin
- lightfast
- high elasticity
- high shock absorption
- individually adjustable hardness
- advanced adhesion when combined with glue
- unplasticized

### Delivery Types

Individually molded profile parts as well as sheets based on customer needs in the size 1,000 x 500 x 1.5 to 10mm.

### Technical Data

Test Property	Method	Unity		
Shore (000)	ASTM D 2240	-	50	65
Density	DIN 53 479	(kg/m <sup>3</sup> )	1700 +/- 100	1600 +/- 100
Tensile strength	ISO 1798	(kPa)	>300	>150
Elongation at Break	ISO 1789	(%)	>600	>600
Thermal Conductivity	ISO 22007	(W/m <sup>2</sup> *K)	0,6	0,85
Temperature Stability	-	°C	-30 to + 80	-30 to + 80

### Standards

Oeko-Tex 100	REACH & RoHS	Aliphatic	UV-Stabilized	Color
no	yes	yes	yes	customizable, base color white

This information is given to the best of our knowledge; however, no legal claim can be derived from this. In case specific questions should arise, please kindly contact our department for application technique.